DINGLI Exceed · New Height

BA18CRT2 Modular Boom Series

SPECIFICATIONS

| Size | Metric | British |
|--------------------------------------|-------------------|----------------------|
| Max. Working Height | 18.11m | 59ft 5in |
| Max. Platform Height | 16.11m | 52ft 10in |
| Max. Operating Range(+0.6m) | 9.45m | 31ft |
| Max. Platform Range | 8.85m | 29ft |
| Flatbed Transport Dimensions (L×W×H) | 5.47m×2.44m×2.59m | 17ft11in×8ft×8ft 6in |
| Standard Container Transport | All Applicable | All Applicable |
| Platform Size(Length×Width) | 1.83m×0.79m | 6ft×2ft7in |
| Turntable Tailswing | 0.13m | 5in |
| Ground Clearance | 0.31m | 1ft |
| Wheelbase | 2.40m | 7ft 10in |
| Turning Radius(Inside/Outside) | 3m/4.73m | 9ft 10in/15ft 6in |
| Tyres | 315/55 D20 | 315/55 D20 |
| Max. Up And Over Clearance | 8.18m | 26ft 10in |
| Max. Down Probing Depth | 0.68m | 2ft 3in |


Performance

| renormance | | |
|----------------------|----------------|----------------|
| S.W.L | 320kg | 705lb |
| Max. Occupants | 2 | 2 |
| Gradeability | 40% | 40% |
| Travel Speed(Stowed) | 6.0km/h | 3.7mph |
| Travel Speed(Raised) | 1.1km/h | 0.7mph |
| Max. Working Slope | X-5°/Y-5° | X-5°/Y-5° |
| Turret Rotation | 360°Continuous | 360°Continuous |
| Platform Rotation | 180° | 180° |
| Jib Movement | 132° | 132° |
| | | |


| Weight | | | |
|----------------|--------|---------|--|
| Overall Weight | 8200kg | 18077lb | |

| Power | | | |
|----------------|------------|---|--|
| Diesel Engine | Kubota D11 | Kubota D1105/18.2kW Kubota D1105/18.2kW | |
| Diesel Tank | 115L | 30gal | |
| Hydraulic Tank | 145L | 38gal | |





Range Of Motion







BA18CRT2 Modular Boom Series

FEATURES

Standard Items

- 1.50m (4ft 11in) Jib
- Front Oscillating Axle
- Two-Wheel Steering
- Four-Wheel Drive
- Self-Leveling Platform
- 180° Left And Right Swing Platform
- Proportional Joystick Controls
- Thumb Rocker Steer
- Drive Enable
- Ac Power Cord To Platform
- Tilt Alarm
- Descent Alarm
- Flash
- Horn
- Hour Meter
- Integral Integrated Special Drive Axle For Construction Machinery
- 360° Continuous Turntable Rotation
- Positive Traction Four Wheel Drive
- Platform Load Sense System
- Fault Diagnosis System
- Operator Anti-crushing Protection System
- Harsh Environment Kits
- 12V DC Auxiliary Power
- Kubota D1105 18kW 2600rpm Diesel Engine
- Hydraulic Oil Radiator
- Anti-restart Engine Protection
- Anti-reverse Engine Device
- Auto Engine Fault Shutdown







Articulated Boom-BA Working Height-18m Diesel Engine

Rough Terrain-RT



Jib

ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688

E-Mail: export@cndingli.com

Https://en.cndingli.com

Due to continuous technology updates, technical parameters are subject to change without notice. This picture book is for reference only, the actual product shall prevail. The copyright is owned by zhejiang dingli, any content may not be copied for any purpose without written permission. 2023-07

